



band detail			
paving slab location at principal ent.			
150mm conc. floor			
dpm lapped up conc. edge			
dpc behind and under cill			
100mm insulation (kingspan or equal app.)			
1200 gauge dpm			
50mm min sand blinding			
150mm min hardcore			
100mm brick/block inner leaf			
102.5mm facing brick colour to be determined			
102.5mm facing brick colour to be determined contrasting to main bwk			
75 mm ECO Cavity board insulation with a 50mm void in cavity.			

KEY TO MASONRY SCHEDULE			
	Facing Brickwork 102.5mm thick by PD Edenhall or equal approved		
	Cavity wall insulation to be ECO Cavity rigid board 75mm thk with 50mm cavity void.		
	Dense blockwork 100mm thick unless noted otherwise		
	Stud partitions ex.75x50 studs at 400 centres with plasterboard and skim		

OPENING SCHEDULE			
opening ref	opening size	lintel ref	lintel size
W1	1472.5x1500	L1/HD110	1800
W2	910x1050	L1/S 110	1200
W3	1810x1200	L1/HD110	2100
W4	685x1050	L1/S 110	1050
W5	1585x1200	L1/HD110	1950
ED1	1022.5x2100	L1/HD110	1350
ED2	1247.5x2100	L1/S 110	1650
D1	910x2100	L1/HD110	1200
D2	910x2100	L1/S 110	1200
D3	910x2100	L1/HD110	1200
D4	910x2100	L1/HD110	1200
Lintel references as IG Lintels Ltd			

INTERNAL DOOR LEAF SCHEDULE	
D1	838x1981high
D2	838x1981high
D3	838x1981high
D4	762x1981high
D5	762x1981high
D6	762x1981high
D7	762x1981high
D8	762x1981high
D9	686x1981high
D10	686x1981high

